Title: Valve Assembly For A Prosthetic Limb

App. No.: 08/947,668 Inventor: Tracey C. Slemker Examiner: David H. Willse

Amendment(s) to the Claims

The following listing of claims replaces all prior versions and listings of claims in

the present application:

**Listing of Claims:** 

- Claims 1-42 (canceled).

- Claim 43 (withdrawn): The prosthetic limb of claim 67, further comprising a sleeve to

be worn over the residual limb.

- Claim 44 (currently amended): A prosthetic limb socket and valve assembly,

comprising:

a non-porous sleeve to be worn over the a residual limb, said sleeve having an

inner surface and an outer surface;

a base attached to an interior distal end of the socket, said base having a

proximate surface facing positioned to face a distal end of a the residual limb upon its

insertion into said socket, and including at least one channel interior thereto for

connecting said proximate surface to the exterior of said socket, said base located

within said socket such that said channel remains unblocked by said residual limb until

said residual limb is fully inserted into said socket;

a duct extending through said socket and connected to said channel; and

a valve coupled to said duct for controlling the flow of air through said channel

caused by insertion of said residual limb into said socket;

wherein the liner sleeve-covered residual limb is retained in said socket by

means of suction a vacuum created by expelling the air in said socket through said

Title: Valve Assembly For A Prosthetic Limb

App. No.: 08/947,668 Inventor: Tracey C. Slemker

Examiner: David H. Willse

valve assembly, said vacuum maintained by sealing contact between said outer surface

of said sleeve and interior walls of said socket; and

wherein substantially no air pockets are left in said socket once said residual limb

has been fully inserted therein.

- Claim 45 (previously presented): The prosthetic limb and valve assembly of claim 44,

wherein said valve is coupled to a pump which provides a forced transfer of air to or

from the socket interior.

Claim 46 (previously presented): The prosthetic limb and valve assembly of claim 44,

wherein said base includes an attachment means adapted to releasably attach an

upright assembly to the distal end of the socket.

Claim 47 (previously presented): The prosthetic limb and valve assembly of claim 44,

wherein said base is adapted to be removably fitted within the socket interior at the

distal end of the socket.

Claim 48 (previously presented): The prosthetic limb and valve assembly of claim 44,

wherein said base includes a proximate cushion portion.

- Claim 49 (canceled).

Claim 50 (currently amended): A prosthetic limb comprising:

a non-porous sleeve to be worn over the residual limb;

a socket having an interior configured to contain a wearer's sleeve-covered

residual limb, a distal end, and an inner surface that provides sealing contact with a

substantial portion of an outer surface of said sleeve; and

a valve assembly removably coupled to the distal end of the socket, and

providing fluid communication with the socket interior, said valve assembly located such

Response Dated: 12/24/2003

Title: Valve Assembly For A Prosthetic Limb

App. No.: 08/947,668 Inventor: Tracey C. Slemker Examiner: David H. Willse

that fluid transfer from within said socket is enabled prior to full insertion of said residual

limb into said socket;

wherein insertion of said residual limb into said socket forces the air in said

socket out through said valve assembly, thereby creating a vacuum within said socket

that retains said residual limb and is maintained by said sealing contact between said

inner surface of said socket and said outer surface of said sleeve; and

wherein substantially no air pockets are left in said socket once said residual limb

has been fully inserted therein.

- Claim 51 (previously presented): The prosthetic limb of claim 50, wherein said valve is

coupled to a pump which provides a forced transfer of air to or from the socket interior.

- Claim 52 (previously presented): The prosthetic limb of claim 50, further comprising a

base attached to the interior distal end of the socket, having a proximate surface,

including at least one channel extending through said proximate surface.

- Claim 53 (previously presented): The prosthetic limb of claim 52, wherein said base is

adapted to be removably fitted within the socket interior at the distal end of the socket.

- Claim 54 (previously presented): The prosthetic limb of claim 52, wherein said base

includes an attachment means adapted to releasably attach an upright assembly to the

distal end of the socket.

- Claim 55 (previously presented): The prosthetic limb of claim 52, wherein said base

includes a proximate cushion portion.

- Claim 56-63 (canceled).

Claim 64 (withdrawn): A valve assembly for a prosthetic limb socket, comprising:

- Claim

Response Dated: 12/24/2003

Title: Valve Assembly For A Prosthetic Limb

App. No.: 08/947,668 Inventor: Tracey C. Slemker

Examiner: David H. Willse

a base adapted to be removably fitted within the socket interior at the distal end

of the socket, said base having a proximate surface, including at least one channel

extending through said proximate surface;

a duct extending through said socket, connected to said channel; and

a valve coupled to said duct for controlling the flow of air therethrough.

- Claim 65 (withdrawn): A method for attaching a prosthesis including a suction socket

having an open proximal end for receiving a residual limb and a distal end, comprising:

(a) rolling a sleeve over the residual limb;

(b) installing a valve means into said distal end of said suction socket, said valve

connected to a duct extending through said socket;

(c) positioning said residual limb with said sleeve into said open proximal end of

said suction socket; and

(d) drawing air through said duct by means of a vacuum pump to create a

negative pressure between said sleeve and said distal end of said suction socket such

that said sleeve is pulled into full engagement within said suction socket.

- Claim 66 (withdrawn): A method for donning or doffing a suction suspension

prosthesis, said prosthesis including a sleeve to be worn over the residual limb, a

suction socket having an open proximal end for receiving said residual limb and said

sleeve and a distal end, comprising:

influencing air pressure between said sleeve and said distal end of said socket;

decreasing the air pressure to a negative pressure to draw said liner and residual

limb into said suction socket or increasing the air pressure to a positive pressure to

6

expel said liner and said residual limb from said suction socket.

Response Dated: 12/24/2003

Title: Valve Assembly For A Prosthetic Limb

App. No.: 08/947,668 Inventor: Tracey C. Slemker

Examiner: David H. Willse

- Claim 67 (withdrawn): A valve assembly for use with a prosthetic limb having a

prosthetic limb socket shaped for receiving a patient's residual limb, the socket having a

socket wall, a socket interior, a proximal opening, and a distal end, the valve assembly

comprising:

a base having a first surface and a second surface, adapted to be fitted within the

socket interior at the distal end of the socket such that said first surface faces the socket

interior and such that said second surface faces the socket wall, said base including a

channel extending therethrough providing fluid communication between said first

surface and said second surface;

a first attachment mechanism, carried on said base, adapted to releasably attach

an upright assembly to the distal end of the socket when said base is fitted within the

socket interior at the distal end of the socket; and

a valve coupled to said base for controlling the flow of air through sad channel.

Claim 68 (withdrawn): The valve assembly of claim 67, wherein said valve assembly

further comprises a seal extending from said base, adapted to provide an air-tight seal

between said base and the socket wall when said base is fitted within the socket interior

at the distal end of the socket.

- Claim 69 (withdrawn): The valve assembly of claim 68, further comprising:

a cushion carrier on said base, having a proximate end and a distal end, said

proximate end being adapted to abut a wearer's residual limb.

- Claim 70 (withdrawn): The valve assembly of claim 69, wherein said cushion is formed

from an elastomeric material and said cushion includes said seal.

Response Dated: 12/24/2003

Title: Valve Assembly For A Prosthetic Limb

App. No.: 08/947,668 Inventor: Tracey C. Slemker

Examiner: David H. Willse

- Claim 71 (withdrawn): The valve assembly of claim 67, wherein said base includes a

second attachment mechanism adapted to releasably attach said base within the socket

interior.

- Claim 72 (withdrawn): The valve assembly of claim 71, wherein said first and said

second attachment mechanisms include a screw- or bolt-receiving hole extending into

said base.

- Claim 73 (withdrawn): The valve assembly of claim 67, wherein said valve includes an

open/close port, said open/close port allowing transfer of air through said valve when

said open/close port is open.

- Claim 74 (withdrawn): The valve assembly of claim 67, wherein said first attachment

mechanisms include a screw- or bolt-receiving hole extending into said base.

- Claim 75 (withdrawn): The valve assembly of claim 74, wherein said screw- or bolt-

receiving hole is threaded.

- Claim 76 (withdrawn): A valve assembly for use with a prosthetic limb having a

prosthetic limb socket shaped for receiving a patient's residual limb, the socket having a

socket wall, a socket interior, a proximal opening, and a distal end, the valve assembly

comprising:

a base including a flexible exterior, a chamber therewithin, and at least one

channel extending into said chamber, said channel being adapted to provide fluid

communication between said chamber and the interior of the socket when said base is

fitted within the socket interior at the distal end of the socket;

a duct engaged with said base and in fluid communication with said chamber;

and

Response Dated: 12/24/2003

Title: Valve Assembly For A Prosthetic Limb

App. No.: 08/947,668 Inventor: Tracey C. Slemker

Examiner: David H. Willse

a valve coupled to said duct for controlling the flow of air therethrough;

whereby said base is adapted to be inserted through the proximal opening and

fitted within the said socket interior at the distal end of the socket, and said flexible

exterior is adapted to abut the socket wall so as to provide an airtight seal between said

base and the socket wall when the base is fitted within the socket interior at the distal

end of the socket.

- Claim 77 (withdrawn): The valve assembly of claim 76, further comprising an

attachment mechanism carried on a distal end of said base, said attachment

mechanism being adapted to secure said base within the distal end of a socket and to

attach an upright assembly to the distal end of the socket.

- Claim 78 (withdrawn): The valve assembly of claim 77, wherein said attachment

mechanism includes a screw- or bolt-receiving hole extending into a distal surface of

said base.

- Claim 79 (currently amended): A prosthetic limb, comprising:

a prosthetic limb socket shaped for receiving a patient's residual limb, said

socket having a socket wall, a socket interior, a proximal opening, and a distal end;

an upright a prosthetic limb assembly for attachment to said prosthetic limb

socket;

a base fitted within said socket interior at said distal end of said socket, <u>a</u>

periphery of said base providing an air-tight seal with said socket wall, said base further

including a channel extending into said base and opening onto said socket interior;

Response Dated: 12/24/2003

Title: Valve Assembly For A Prosthetic Limb

App. No.: 08/947,668 Inventor: Tracey C. Slemker Examiner: David H. Willse

an attachment mechanism, carried on said base, for releasably attaching

facilitating releasable attachment of said upright prosthetic limb assembly to an exterior

distal end of said socket; and

a valve coupled to said base for controlling the flow of air through said channel.

- Claim 80 (currently amended): The prosthetic limb of claim 79, further comprising

wherein a substantially annular projection extending from said base and providing an is

used to provide said air-tight seal between said base and said socket wall.

- Claim 81 (previously presented): A prosthetic limb, comprising:

a prosthetic limb socket shaped for receiving a patient's residual limb, said

socket having a socket wall, a socket interior, a proximal opening, and a distal end;

an upright assembly;

a base-plate fitted within said socket interior at said distal end of said socket, said

base-plate including a channel extending into said base-plate and opening onto said

socket interior;

a valve coupled to said base-plate for controlling the flow of air through said

channel; and

a bolt extending from said upright assembly, through said socket wall and into

said base-plate;

whereby said base-plate facilitates the passage of air from said socket interior

and also facilitates the coupling of the upright assembly to an exterior distal end of said

socket.

- Claim 82 (previously presented): The prosthetic limb of claim 81, further comprising an

air-tight seal between said base-plate and said socket wall.

Response Dated: 12/24/2003

Title: Valve Assembly For A Prosthetic Limb

App. No.: 08/947,668 Inventor: Tracey C. Slemker Examiner: David H. Willse

- Claim 83 (currently amended): A prosthetic limb, comprising:

a prosthetic limb socket shaped for receiving a patient's residual limb, said socket having a socket wall, a an open socket interior formed by walls and a bottom, a

proximal opening, and a distal end;

a base-plate fitted within said socket interior at said distal end of said socket

bottom thereof, said base-plate including a channel extending into said base-plate and

opening onto said socket interior; and

a port communicating with said channel, said port facilitating the coupling of a

pump thereto so as to provide a forced transfer of air to or from said open socket interior

through said channel and said base-plate;

whereby said residual limb can be drawn into or forced out of said prosthetic limb

socket by said forced transfer of air; and

wherein substantially no air pockets remain within said prosthetic limb socket

when said residual limb has been fully drawn into said socket.